

ESTTA Tracking number: **ESTTA727665**

Filing date: **02/17/2016**

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
BEFORE THE TRADEMARK TRIAL AND APPEAL BOARD

Proceeding	92053247
Party	Defendant VARTA Microbattery GmbH
Correspondence Address	H DAVID STARR NATH GOLDBERG & MEYER 112 S WEST STREET ALEXANDRIA, VA 22314 UNITED STATES dstarr@nathlaw.com, gbennett@nathlaw.com
Submission	Motion to Amend Registration
Filer's Name	H. David Starr
Filer's e-mail	dstarr@nathlaw.com
Signature	/H. David Starr/
Date	02/17/2016
Attachments	Consented Motion To Amend and Dismiss.final.pdf(13421 bytes) Exhibit A.final.pdf(1149187 bytes)

Registration Subject to the filing

Registration No	3669642	Registration date	08/18/2009
International Registration No.	NONE	International Registration Date	NONE
Registrant	VARTA Microbattery GmbH Daimlerstraße 1 GERMANY		

Goods/Services Subject to the filing

Class 009. First Use: 0 First Use In Commerce: 0

All goods and services in the class are requested, namely: Batteries, accumulators, galvanic cells, electric primary and secondary cells, microbatteries, equipment batteries, lithium batteries, lithium accumulators, zinc air batteries, nickel-metal hydride batteries; fuel elements and fuel cells; gas generating cells, in particular cells for generating oxygen and hydrogen; equipment and apparatus for charging, testing, maintaining and monitoring the aforesaid goods; rectifiers, switching equipment, switches and capacity meters for all the aforesaid goods

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
BEFORE THE TRADEMARK TRIAL AND APPEAL BOARD**

Johnson Controls Technology Company,

Petitioner,

and

Johnson Controls Hybrid and Recycling GmbH,
Petitioner,

Cancellation No. 92053247

v.

VARTA Microbattery GmbH,

Respondent

CONSENTED MOTION TO AMEND AND DISMISS

VARTA Microbattery GmbH (“Varta”), with the express consent of Johnson Controls Technology Company and Johnson Controls Hybrid and Recycling GmbH (collectively “Johnson Controls”) set forth below, hereby moves to amend subject US Registration no. 3669642 pursuant to the Settlement Agreement reached between the parties. Particularly, Varta moves to amend the identification to the following:

“Batteries, accumulators, galvanic cells, electric primary and secondary cells, all the aforementioned with a cell height of not larger than 11 mm, or with a cell height over 11 mm, but not more than 25 mm, provided that the height/diameter ratio is not more than 1,” in International Class 9.

Varta is concurrently submitting its Declaration of Use consistent with the amended identification, which is attached hereto as Exhibit “A”.

Upon entry of the amended identification by the Board, the parties jointly request dismissal of this proceeding without prejudice.

Dated: February 17, 2016

Respectfully submitted,

AGREED AND ACKNOWLEDGED

/s/H. David Starr

H. David Starr

Attorney for VARTA Microbattery GmbH

Nath, Goldberg & Meyer

112 S. West Street

Alexandria, VA 22314

(703) 548-6284 Phone

(703) 683-8396 Fax

/s/ Kelu L. Sullivan

Kelu Sullivan

Attorney for Johnson Controls

Technology Company and Johnson

Controls Hybrid and Recycling GmbH

CERTIFICATE OF SERVICE

This is to certify that I am on this 17th day of February 2016 serving a copy of the within and foregoing upon the attorneys for Johnson Controls Technology Company and Johnson Controls Hybrid and Recycling GmbH via electronic mail return receipt requested, addressed as follows:
ksullivan@bakerlaw.com, bhipdocket@bakerlaw.com.

/s/H. David Starr_____
H. David Starr

EXHIBIT “A”

Trademark Electronic Application System (TEAS) filing receipt

'3669642'. A summary of your submission is listed below. If you determine that you made an error in the information you entered, **DO NOT** request any changes by e-mail, because the TEAS Support Team cannot make corrections. You may submit a new document and new fees, if time remains in the statutory period; however, the USPTO will not refund any fees paid as part of this current submission. For further information, please contact the Post Registration Division at (571) 272-9500, and ask to speak to an Affidavit Renewal Examiner. Or, see Chapter 1600 of the Trademark Manual of Examining Procedure, at <http://tess2.uspto.gov/tmdb/tmep/1600.htm>

REGISTRATION NUMBER: 3669642

REGISTRATION DATE: 08/18/2009

MARK: (Stylized and/or with Design, Miscellaneous Mark)

The owner/holder, VARTA Microbattery GmbH, GmbH legally organized under the laws of Germany, having an address of

Daimlerstraße 1
Ellwangen, 73479
Germany

is filing a Declaration of Continued Use/Excusable Nonuse of Mark in Commerce Under Section 71.

For International Class 009, this filing does **NOT** cover the following goods or services for this specific class listed in the registered extension of protection, and these goods or services are to be permanently **deleted (removed)** from the registration: microbatteries, equipment batteries, lithium batteries, lithium accumulators, zinc air batteries, nickel-metal hydride batteries; fuel elements and fuel cells; gas generating cells, in particular cells for generating oxygen and hydrogen; equipment and apparatus for charging, testing, maintaining and monitoring the aforesaid goods; rectifiers, switching equipment, switches and capacity meters for all the aforesaid goods

The mark is in use in commerce on or in connection with the following goods/services, or to indicate membership in the collective membership organization, listed in the existing registered extension of protection for this specific class; or, the owner is making the listed excusable nonuse claim: Batteries, accumulators, galvanic cells, electric primary and secondary cells, all the aforementioned with a cell height of not larger than 11 mm, or with a cell height over 11 mm, but not more than 25 mm, provided that the height/diameter ratio is not more than 1

The owner is submitting one(or more) specimen(s) showing the mark as used in commerce on or in connection with any item in this class, consisting of a(n) label showing use of mark with goods; safety data sheet; data sheet.

1 [SPN0-5076749-20160216095337343572_._20160216094108.pdf]

2 [SPN0-5076749-20160217165418230845_._MSDS_05_Primary_Lithium_Button_Series_CR_en.pdf]

3 [SPN0-5076749-20160217165418230845_._CR2032_DS_.pdf]

MISCELLANEOUS STATEMENTS

This registration is subject to Cancellation No.92053247. A Consented Motion to Amend and Dismiss is being filed therein.

The registrant's current Correspondence Information: H DAVID STARR of NATH GOLDBERG & MEYER

112 S WEST STREET
ALEXANDRIA, Virginia 22314
United States

The registrant's proposed Correspondence Information: H. David Starr of Nath, Goldberg & Meyer

112 S WEST STREET
ALEXANDRIA, Virginia 22314
United States

The docket/reference number is 61950.

The phone number is 7035486284.

The fax number is 7036838396.

The email address is dstarr@nathlaw.com;docketing@nathlaw.com.

The registrant hereby appoints H. David Starr and Gary M. Nath, Joshua B. Goldberg, Howard W. Kline, Jerald L. Meyer of Nath, Goldberg & Meyer

112 S West Street
Alexandria, Virginia 22314
United States

to submit this Declaration of Continued Use/Excusable Nonuse of Mark in Commerce Under Section 71 on behalf of the registrant. The docket/reference number is 61950.

The phone number is 7035486284.

The fax number is 7036838396.

The email address is dstarr@nathlaw.com.

A fee payment in the amount of \$200 was submitted with the form, representing payment for 1 class(es), plus any additional grace period fee, if necessary.

Declaration

Unless the owner/holder has specifically claimed excusable nonuse, the mark is in use in commerce on or in connection with the goods/services, or to indicate membership in the collective organization identified above, as evidenced by the attached specimen(s) showing the mark as used in commerce.

The signatory being warned that willful false statements and the like are punishable by fine or imprisonment, or both, under 18 U.S.C. §1001, and that such willful false statements and the like may

jeopardize the validity of this submission, declares that all statements made of his/her own knowledge are true and all statements made on information and belief are believed to be true.

Signature: /H. David Starr/ Date: 02/17/2016

Signatory's Name: H. David Starr

Signatory's Position: Attorney for Registrant, District of Columbia bar member

Thank you,

The TEAS support team

Wed Feb 17 16:59:24 EST 2016

STAMP: USPTO/SECT71-50.76.7.49-20160217165924058524-3669642-

5502ffa6b2fb27e83591c17d6e6210b3619f9dd48c253068ea5d7291be412189e2-CC-3851-

20160217165418230845

Under the Paperwork Reduction Act of 1995 no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PTO Form 1663 (Rev 11/2012)

OMB No. 0651-0055 (Exp 12/31/2018)

Declaration of Continued Use/Excusable Nonuse of Mark in Commerce Under Section 71

To the Commissioner for Trademarks:

REGISTRATION NUMBER: 3669642

REGISTRATION DATE: 08/18/2009

MARK: (Stylized and/or with Design, Miscellaneous Mark)

The owner/holder, VARTA Microbattery GmbH, GmbH legally organized under the laws of Germany, having an address of

Daimlerstraße 1

Ellwangen, 73479

Germany

is filing a Declaration of Continued Use/Excusable Nonuse of Mark in Commerce Under Section 71.

For International Class 009, this filing does **NOT** cover the following goods or services for this specific class listed in the registered extension of protection, and these goods or services are to be permanently **deleted (removed)** from the registration: microbatteries, equipment batteries, lithium batteries, lithium accumulators, zinc air batteries, nickel-metal hydride batteries; fuel elements and fuel cells; gas generating cells, in particular cells for generating oxygen and hydrogen; equipment and apparatus for charging, testing, maintaining and monitoring the aforesaid goods; rectifiers, switching equipment, switches and capacity meters for all the aforesaid goods

The mark is in use in commerce on or in connection with the following goods/services, or to indicate membership in the collective membership organization, listed in the existing registered extension of protection for this specific class; or, the owner is making the listed excusable nonuse claim: Batteries, accumulators, galvanic cells, electric primary and secondary cells, all the aforementioned with a cell height of not larger than 11 mm, or with a cell height over 11 mm, but not more than 25 mm, provided that the height/diameter ratio is not more than 1

The owner is submitting one(or more) specimen(s) showing the mark as used in commerce on or in connection with any item in this class, consisting of a(n) label showing use of mark with goods; safety data sheet; data sheet.

[Specimen-1](#) [SPN0-5076749-20160216095337343572_._20160216094108.pdf]

[Specimen-2](#) [SPN0-5076749-

20160217165418230845_._MSDS_05_Primary_Lithium_Button_Series_CR_en.pdf]

[Specimen-3](#) [SPN0-5076749-20160217165418230845_._CR2032_DS_.pdf]

MISCELLANEOUS STATEMENTS

This registration is subject to Cancellation No.92053247. A Consented Motion to Amend and Dismiss is being filed therein.

The registrant's current Correspondence Information: H DAVID STARR of NATH GOLDBERG & MEYER
112 S WEST STREET
ALEXANDRIA, Virginia 22314
United States

The registrant's proposed Correspondence Information: H. David Starr of Nath, Goldberg & Meyer
112 S WEST STREET
ALEXANDRIA, Virginia 22314
United States
The docket/reference number is 61950.

The phone number is 7035486284.

The fax number is 7036838396.

The email address is dstarr@nathlaw.com; docketing@nathlaw.com.
The registrant hereby appoints H. David Starr and Gary M. Nath, Joshua B. Goldberg, Howard W. Kline, Jerald L. Meyer of Nath, Goldberg & Meyer
112 S West Street
Alexandria, Virginia 22314
United States

to submit this Declaration of Continued Use/Excusable Nonuse of Mark in Commerce Under Section 71 on behalf of the registrant. The docket/reference number is 61950.

The phone number is 7035486284.

The fax number is 7036838396.

The email address is dstarr@nathlaw.com.

A fee payment in the amount of \$200 will be submitted with the form, representing payment for 1 class(es), plus any additional grace period fee, if necessary.

Declaration

Unless the owner/holder has specifically claimed excusable nonuse, the mark is in use in commerce on or in connection with the goods/services, or to indicate membership in the collective membership organization identified above, as evidenced by the attached specimen(s) showing the mark as used in commerce.

The signatory being warned that willful false statements and the like are punishable by fine or imprisonment, or both, under 18 U.S.C. § 1001, and that such willful false statements and the like may jeopardize the validity of this submission, declares that all statements made of his/her own knowledge are true and all statements made on information and belief are believed to be true.

Signature: /H. David Starr/ Date: 02/17/2016

Signatory's Name: H. David Starr

Signatory's Position: Attorney for Registrant, District of Columbia bar member

[Back](#)

VARTA

CR2032

640 pcs

Lithium 3V

WARNING

Read all parts of English
The VARTA warning:
Lithium is not to be
disposed of as an fire.

6032 501 501 / 692944



043752 295856

90




CAUTION!

Do not use battery in case
of fire and heat
A package is not to be
disposed of as an fire
The VARTA warning:
Lithium is not to be
disposed of as an fire.



Made in PRC

5355

Data Sheet


Type Number	6032
Designation IEC	CR 2032
System	Li-Manganese dioxide / Organic Electrolyte
UL Recognition	MH 13654 (N)
Nominal Voltage	3 V
Typical Capacity C	230 mAh
Load 5.6 kOhm, at 20°C down to 2 V	
Weight (approx.)	3 g
Volume	0,95 ccm
Coding	Date of Manufacturing Month / Year
Temperature Ranges	min. max.
Storage	- 55°C 70°C
Discharge	- 20°C 70°C*
Dimensions	min. max.
Diameter (A)	19,70 20,00
Height (B)	2,90 3,20
Shoulder Diameter (E)	16,00

Typical Capacities (at 20°C)

Discharge Type	Load	End Voltage:	2.0 V
Continuous	5600 Ω	Time:	460 h
24h / d, 7d / w		Capacity [mAh]:	230
Current [μA]:		Energy [mWh]:	645

* Contact VARTA if the application is intended to be outside the range of -20°C to +70°C.

*Information and contents in this data sheet are for reference purpose only.
They do not constitute any warranty or representation and are subject to change without notice.
For most current information and further details, please contact your VARTA representative.*

VARTA Microbattery GmbH, Daimlerstr. 1, D-73479 Ellwangen/Jagst

Subject to change without prior notice!


Tel.: (+49) 7961/921-0, Telefax: (+49) 7961/921-553

Date of issue: 2014-09-16


Data Sheet

Performance Data:

- Temperature Characteristics**




- Operating Voltage vs. load resistance ***



* Voltage at 50% discharge depth

- Capacity vs. load resistance**



- Self-discharge rate < 1% at room temperature
- Storage life > 10 years
- Operating life* > 10 years

* depending on environmental condition and energy consumption

Information and contents in this data sheet are for reference purpose only.
They do not constitute any warranty or representation and are subject to change without notice.
For most current information and further details, please contact your VARTA representative.

VARTA Microbattery GmbH, Daimlerstr. 1, D-73479 Ellwangen/Jagst

Tel.: (+49) 7961/921-0, Telefax: (+49) 7961/921-553

Date of issue: 2014-09-16

Subject to change without prior notice!

Lithium primary button cell

1. Identification of the product and of the company undertaking

Product details

Trade name:	Lithium primary button cell
Voltage:	3.0 V (or multiples of this in case of multi-cell configurations)
Electrochemical system:	Lithium metal organic electrolyte manganese dioxide
Anode (negative):	Lithium metal
Cathode (positive):	Manganese dioxide

Type:	Lithium content per cell:
CR 1025	0,009 g
CR 1216	0,008 g
CR 1220	0,01 g
CR 1225	0,015 g
CR 1616	0,02 g
CR 1620	0,02 g
CR 1632	0,04 g
CR 2016	0,03 g
CR 2016-P	0,03 g
CR 2025	0,05 g
CR 2025-P	0,05 g
CR 2032	0,07 g
CR 2032-P	0,07 g
CR 2320	0,043 g
CR 2430	0,09 g
CR 2430-P	0,09 g
CR 2450	0,17 g
CR 2450-P	0,17 g
CR 1/3 N	0,06 g
p 28 pxl	0,05 g

Supplier details

Address:	VARTA Microbattery GmbH Daimlerstr. 1 D-73479 Ellwangen/Jagst Germany
Emergency telephone number:	+49 7961 921 110 (VAC)

Legal Remark (U.S.A.)

Safety Data Sheets are a sub-requirement of the Occupational Safety and Health Administration (OSHA) Hazard Communication Standard, 29 CFR Subpart 1910.1200. This Hazard Communication Standard does not apply to various subcategories including anything defined by OSHA as an "article". According to OSHA, Article means a manufactured item other than a fluid or particle: (i) which is formed to a specific shape or design during manufacture; (ii) which has end use function(s) dependent in whole or in part upon its shape or design during end use; and (iii) which under normal conditions of use does not release more than very small quantities, e.g., minute or trace amounts of a hazardous chemical (as determined under paragraph (d) of this section), and does not pose a physical hazard or health risk to employees.

Because all of our batteries are defined as "articles", they are exempted from the requirements of the Hazard Communication Standard.

Legal remark (EU)

These batteries are no "substances" or "mixtures" according to Regulation (EC) No 1907/2006 EC. Instead they have to be regarded as "articles", no substances are intended to be released during handling. Therefore there is no obligation to supply a "safety data sheet according to Regulation (EC) 1907/2006, Article 31".

General remark

This Safety Data Sheet is provided as a service to our customers. The details presented are in accordance with our present knowledge and experiences. They are no contractual assurances of product attributes.

2. Hazards identification

The battery is sealed hermetically. Thus, the ingredients have no hazard potential, except the battery is violated or dismantled.

If in case of mistreatment the ingredients are released, a spontaneously flammable gas mixture may be released under certain circumstances (measures according to chapter 4 to 6).

Attention: If batteries are treated wrong the danger of burns or bursts occurs. Batteries must not be heated above 100°C or incinerated. The battery contents must not get in contact with water. If the negative electrode gets in contact with water or humidity hydrogen gas is formed, which may inflame spontaneously.

3. Composition/information on ingredients

Ingredients

Contents	CAS No.	Hazard Categories	Hazard Statements	Material
1 - 3 %	7439-93-2	Water-react. 1 Skin Corr. 1B	H260 H314	Lithium
13 - 40 %	1313-13-9	Acute Tox. 4	H302 H332	Manganese dioxide
< 10 %	108-32-7	Eye Irrit. 2	H319	Propylene carbonate
< 10 %	110-71-4	Flam. Liq. 2 Repr. 1B Acute Tox. 4	H225 H360-FD H332	1,2-Dimethoxy ethane
< 5 %	646-6-0	Flam. Liq. 2	H225	1,3-Dioxolane
< 5 %	7791-03-9	Ox. Sol. 2 Skin Irrit. 2 Eye Irrit. 2 STOT SE 3	H272 H315 H319 H335	Lithium perchlorate (CR 123 A -R and CR 2 -R only)

Full text of Hazard statements: see section 16.

Heavy Metals

Contents	CAS No.	Material
< 1 mg/kg	7440-43-9	Cadmium
< 10 mg/kg	7439-92-1	Lead
< 0,1 mg/kg	7439-97-6	Mercury (none intentionally introduced, see Chapter 12)
< 5 mg/kg		Hexavalent Chromium (Cr ⁶⁺)

Other Ingredients

Contents	CAS No.	Material
33 - 74 %		Steel and nickel
3 - 10 %		Plastic

SVHC substances according to REACH (Article 33)

Contents	EC No.	CAS No.	Material
> 0.1 %	203-794-9	110-71-4	1,2-dimethoxyethane; ethylene glycol dimethyl ether (EGDME)

For information to allow safe use: see section 7.

4. First-aid measures

Measures at accidental release

After inhalation:	Fresh air. Seek for medical assistance.
After skin contact:	Remove solid particles immediately. Flush affected areas with plenty of water (at least 15 min.). Remove contaminated cloth immediately. Seek for medical assistance.
After eye contact:	Flush the eye gently with plenty of water (at least 15 min.). Seek for medical assistance.
After ingestion:	Drink plenty of water. Avoid vomiting. Seek for medical assistance. No trials for neutralization. Further advice for the medical sector: http://buttonbatterysafety.com/ See also Chapter 7.

5. Fire-fighting measures

Suitable extinguishing media:	Metal fire extinction powder, rock salt or dry sand shall be used. In case only water is available, it can be used in large amounts.
Extinguishing media with limited suitability:	Carbon dioxide (CO ₂) is not suitable. Water in small quantities may have adverse effects.
Special protection equipment during fire-fighting:	Protective clothing including breathing apparatus.
Special hazard:	Cells may explode and release metal parts. At contact of anode material with water extremely flammable hydrogen gas and caustic liquid are released.
Attention:	Do not let used extinguishing media penetrate into surface water or ground water. Dispose off properly.

6. Accidental release measures

Person related measures:	Wear personal protective equipment adapted to the situation (protection gloves, cloth, face protection, breathing protection).
Environment protection measures:	Bind released ingredients with powder (rock salt, sand). Dispose off according to the local law and rules. Avoid leached substances to penetrate into the earth, canalization or water.
Treatment for cleaning:	If battery casing is dismantled, small amounts of electrolyte may leak. Package the battery tightly including ingredients together with lime, sand or rock salt. Then clean with water.

7. Handling and storage

Guideline for safe handling:

Always follow the warning information on the batteries and in the manuals of devices. Only use the recommended battery types.

Keep batteries away from children.

For devices to be used by children, the battery casing should be protected against unauthorized access.

Unpacked batteries shall not lie about in bulk.

In case of battery change always replace all batteries by new ones of identical type and brand.

Do not swallow batteries.

Do not throw batteries into water.

Do not throw batteries into fire.

Do not short-circuit batteries.

Do not recharge primary batteries.

Do not open or disassemble batteries.

Further advice for parents: <http://buttonbatterysafety.com/>

Supply to private end users:

In case the products are supplied to private end users packed with equipment or contained in equipment it is strongly recommended to follow UL product and instruction manual requirements:

The product is required to be marked with a graphical symbol that alerts the user to refer to the instruction manual.

The instruction manual itself is required to contain

- a warning marking with text to alert the user of the potential chemical burn hazard associated with coin/button battery ingestion,

- an instruction as to the presence of a coin/button cell battery,

- possible effects of battery ingestion,

- an instruction to keep batteries away from children,

- an advice to seek immediate medical attention if it suspected that batteries have either been swallowed or placed inside any part of the body.

Storage:

Storage preferably at room temperature (approx. 20°C). Avoid large temperature changes. Avoid direct sunlight. At higher temperature the electrical performance may be reduced.

Storage of unpacked batteries can cause short circuit and heat generation.

Storage category

according to TRGS 510:

It is recommended to consider the "Technical Rule for Hazardous Substances TRGS 510 - Storage of hazardous substances in nonstationary containers" and to handle lithium primary button cells according to storage category 11 ("combustible solids").

Storage of large amounts:

Follow the recommendations of the German Insurance Association (GDV - "Gesamtverband der Deutschen Versicherungswirtschaft e.V.") concerning lithium batteries:

http://vds.de/fileadmin/vds_publicationen/vds_3103_web.pdf

In case of storage of large amounts (used storage volume > 7 m³ and/or more than 6 pallets) batteries shall be stored in fire-resistant or separated rooms or areas (e.g. warehouse or container for hazardous materials). Mixed storage with other products is not allowed. The storage area shall be monitored by an automatic fire detection system, connected to a permanently manned place. A fire-extinguishing system shall reflect the extinguishing agents mentioned in chapter 5.

8. Exposure controls/personal protection

Under normal conditions (during discharge) release of ingredients does not occur.

9. Physical and chemical properties

Not applicable if closed.

10. Stability and reactivity

Dangerous reactions:

When heated above 100°C the risk of rupture occurs.

11. Toxicological information

Under normal conditions (during charge and discharge) release of ingredients does not occur. In case of accidental release see information in chapter 2.

Swallowing of a battery can be harmful. Call the local Poison Control Centre for advice and follow-up.

12. Ecological information

Lithium primary button cells manufactured by VARTA Microbattery do not contain heavy metals as defined by the European directives 2006/66/EC Article 21; they comply with the chemical composition requirements of this Directive.

Mercury has not been "intentionally introduced (as distinguished from mercury that may be incidentally present in other materials)" in the sense of the U.S.A. "Mercury-Containing and Rechargeable Battery Management Act" (May 13 1996).

The Regulation on Mercury Content Limitation for Batteries promulgated on 1997-12-31 by the China authorities including the State Administration of Light Industry and the State Environmental Protection Administration defines 'low mercury' as 'mercury content by weight in battery as less than 0.025%', and 'mercury free' as 'mercury content by weight in battery as less than 0.0001%'. And therefore: Varta lithium primary button cells/batteries belong to the category of mercury-free battery (mercury content lower than 0.0001%).

13. Disposal considerations

USA: Lithium primary button cells are classified by the federal government as non-hazardous waste and are safe for disposal in the normal municipal waste stream.

In the European Union, manufacturing, handling and disposal of batteries is regulated on the basis of the DIRECTIVE 2006/66/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 6 September 2006 on batteries and accumulators and waste batteries and accumulators and repealing Directive 91/157/EEC. Customers find detailed information on disposal in their specific countries using the web site of the European Portable Batteries Association (http://www.epbaeurope.net/legislation_national.html).

Importers and users outside EU should consider the local law and rules.

In order to avoid short circuit and heating, used lithium primary button cells should never be stored or transported in bulk. Proper measures against short circuit are:

- Storage of batteries in original packaging
- Coverage of the terminals
- Embedding in dry sand

14. Transport information

General considerations

Lithium primary button cells manufactured by VARTA Microbattery are considered to be UN3090 Lithium Metal Batteries and are tested according to 38.3 of the "UN Manual of Tests and Criteria" for compliance with the requirements of special provisions ADR 188, IMDG 188, as well as the requirements of DOT / 49 CFR § 173.185, and the General Requirements of IATA DGR packing instruction 968. Positive test results as well as other relevant information required for transportation are stated in dedicated "Declarations of Conformity".

Transportations of cells or batteries packed with equipment or contained in equipment have to follow the appropriate regulations for UN3091.

Compilations of transport requirements for Lithium batteries can be found in:

<https://www.lithium-batterie-service.de/en/>

<http://www.hyperedizioni.com/news/the-lithium-batteries/3139/The-lithium-batteries.html>

USA

Primary (non-rechargeable) lithium batteries and cells are forbidden for transport aboard passenger carrying aircraft. The outside of each package that contains primary (non-rechargeable) lithium batteries or cells must be marked "PRIMARY LITHIUM BATTERIES-FORBIDDEN FOR TRANSPORT ABOARD PASSENGER AIRCRAFT" on a background of contrasting color.

IEC 60086-1

Code of practice for packaging and shipment of primary batteries given in IEC 60086-1:

The packaging shall be adequate to avoid mechanical damage during transport, handling and stacking. The materials and pack design shall be chosen so as to prevent the development of unintentional electrical conduction, corrosion of the terminals and ingress of moisture.

Shock and vibration shall be kept to a minimum. For instance, boxes should not be thrown off trucks, slammed into position or piled so high as to overload battery containers below. Protection from inclement weather should be provided.

15. Regulatory information

Marking consideration:

For the state of California these batteries have to be marked as "containing perchlorate".

According to "DIRECTIVE 2006/66/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 6 September 2006 on batteries and accumulators and waste batteries and accumulators and repealing Directive 91/157/EEC" the batteries have to be marked with the crossed bin. Due to the size of the products the battery need not be marked but a symbol measuring at least 1 × 1 cm shall be printed on the packaging.

International safety standards:

The basis cells are recognized components according to UL 1642.

Water hazard class:

The regulations of the German Federal Water Management Act (WHG) are not applicable as Lithium primary batteries are articles and not substances, thus there is no risk of water pollution, except the batteries are violated or dismantled.

16. Other information

Full text of Hazard Statements referred to under section 3

H225	Highly flammable liquid and vapour.
H260	In contact with water releases flammable gases which may ignite spontaneously.
H272	May intensify fire; oxidizer.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H360FD	May damage fertility. May damage the unborn child.

Note:

Date of issue of the transport regulations: ADR 2015, RID 2015, IATA 2016 (57th edition), IMDG 2014, DOT / 49 CFR 2015.
Latest covered modification of the European Battery Directive 2006/66/EC: Directive 2013/56/EU.

Issued by:

VARTA Microbattery GmbH
Quality / Environmental Management

Contact:

<http://contact.varta-microbattery.com>

Updates:

Current SDS can be downloaded from VARTA's web page following the link:
<http://www.varta-microbattery.com/en/news-downloads/downloads.html>